

G00729 Super Impact Grease

Greases



Features

- 550+ Dropping Point, Non-Melt Grease
- 65 Timken OK Load
- Extreme Tack, Resists Pounding Out
- Great for Heavy Equipment
- Wide Range of Operating Temperatures


Description

This product is a multi-purpose grease fortified with special additives enabling it to withstand the heavy impact and pounding pressures common to heavy equipment. Our special additive package allows the grease to stay in place and not to spatter or pound out of the bearing or fitting. Most greases manufactured today do not have this anti-spatter capability.

TECHNICAL INFO:		
Physical Properties	Appearance	Gel
	Color	Green
	Odor/Fragrance	Petroleum
	pH	N/A
	Spray Pattern	N/A
Environmental Profile	Glycol Ether Content	None
	Biodegradability	No
	Chlorinated Solvents	None
	Green Status	None
	Recyclable Packaging	Yes
Regulatory Profile	% VOC By Weight	3.0
	VOC Restricted Regions	None
	Food Processing Suitability	N/A
	EPA #	N/A
	Flammability per CPSC	N/A
	Flash Point	> 400° F



Packages Available:



Label Datecode: 04/08

Manufactured by:

amrep
PROFESSIONAL PRODUCTS GROUP inc.

990 Industrial Park Drive • Marietta, GA 30062
800-241-7766 • 770-422-2071 • Fax: 770-422-1737
www.amrep.com