



## PRODUCT SPECIFICATION REPORT



# ZEP OVATION™

## High-Solids, Low-Maintenance Floor Finish

### DESCRIPTION

A 25% solids, acrylic copolymer, metal interlock, dry bright floor finish designed for fast gloss build with fewer coats, low maintenance and high durability. Dries to a brilliant, super-hard coating. Excellent resistant to scuffs and black heel marks.

### FEATURES

- Faster gloss build
- Low-maintenance
- Easy to maintain
- Easy to apply
- Easy to strip
- Economical
- Slip-resistant

### BENEFITS

- High-solids content provides maximum gloss with fewer coats. May be damp-mopped daily using neutral detergents, without affecting gloss.
- Dries to a very hard, clear coating, allowing for the use of low-maintenance procedures.
- Dust mop or damp mop with Zep pH Perfect as needed. Designed for low maintenance, but can be spray-buffed to extend times between recoats.
- Easier to apply than other high-solids (25%) finishes. Dries in 30 minutes. Recoats and blends well with existing coats.
- Easily removed with Zep Time Saver, Zep Strip-Ease or any conventional Zep stripper.
- One gallon covers 2000-2500 square feet.
- Meets or exceeds Slip Resistance Standards (when properly maintained) established by CSPA and UL as tested in accordance with ASTM D-2047.

### APPLICATIONS

High-solids, low-maintenance polish used in a wide range of applications on most types of floor surfaces, including rubber, asphalt tile, vinyl, cork, vinyl asbestos, sealed concrete, terrazzo, etc. Particularly useful in:

Airport Terminal Services	Hotels and Motels	Schools & Educational Services	Real Estate Brokers
Child Day Care Services	Nursing Homes & Hospitals	Sports & Recreation Clubs	
Department Stores	Operators of Apartment Buildings	Eating & Drinking Establishments	

### COMPANION PRODUCTS

For spray buffing: Zep Rayon Top Mop, Zep Buff-Up, Zep ZC low-speed floor machine with red pad. For burnishing: Zep Model 20 UHS burnisher, Zep Propane Burnisher, Zep Perimeter and Zep Natural Pad. Also: Zep pH Perfect, Zep Strip-Ease, lamb's wool applicator, Zep Structolene Bucket and Wringer

### SPECIFICATIONS

Physical Form . . . . .Thin, water-based liquid	Solids (non-volatile).....25%
Color . . . . .Opaque, milky-white	Flash Point (TCC) .....None
Odor . . . . .Mild	Shelf Life .....1 year minimum
pH (Concentrate) . . . . .7.5 - 8.5	D.O.T. Shipping Label.....None
Density/Specific Gravity . . . . .8.45 lbs./gal. - 1.01	

### PACKAGING

Gallons  
5-Gallon Pail  
Drums



PRODUCT LABEL

**ZEP OVATION™**  
High-Solids, Low-Maintenance Floor Finish

PROD. #1901  
501F



**ZEP MANUFACTURING COMPANY**  
ATLANTA, GA 30301  
A division of Acuity Specialty Products Group, Inc.  
CLEAN ACROSS AMERICA  
AND THROUGHOUT THE WORLD™



BEFORE USING THIS PRODUCT,  
PLEASE READ THIS ENTIRE LABEL.

**KEEP OUT OF REACH OF CHILDREN**  
FOR INDUSTRIAL AND INSTITUTIONAL  
USE ONLY  
NOT FOR HOUSEHOLD USE OR RESALE

**PRECAUCION**  
AL USUARIO: Si usted no lee inglés, no use este  
producto hasta que la etiqueta le haya sido  
explicada ampliamente.  
(TO THE USER: If you cannot read English, do  
not use this product until the label has been fully  
explained to you.)

This product is designed exclusively for industrial and  
institutional use by trained, professional maintenance  
personnel. Label directions and precautions must be  
followed exactly. Zep Manufacturing Company will not be  
responsible for any injury, loss, or damage if product is  
used in any manner not in compliance with label  
directions, or if precautions are not observed.

**HMS RATINGS**

HEALTH	1	4 EXTREME 3 SERIOUS
FLAMMABILITY	0	2 MODERATE 1 SLIGHT
REACTIVITY	0	0 MINIMAL
PERSONAL PROTECTION EQUIPMENT	A	Glasses

**NEXT**  
**STEP 3**  
FLOOR FINISH

**ZEP OVATION™**  
HIGH SOLIDS, LOW MAINTENANCE FLOOR FINISH

A 25% solids, acrylic copolymer, metal interlock, dry bright floor finish designed for fast gloss build with fewer coats, low maintenance and high durability. Dries to a brilliant, super-hard coating. Excellent resistance to scuffs and black heel marks. Dries in 30 minutes. Coverage is 2000-2500 square feet per gallon. For use on all types of flooring including rubber, asphalt tile, vinyl, cork, vinyl asbestos, sealed concrete, terrazzo, etc.

Meets or exceeds Slip Resistance Standards, (when properly maintained), established by CSPA and UL as tested in accordance with ASTM D-2047.

**DIRECTIONS:**

1. For best results, strip all old finish using Zep Time Saver stripper or Zep Strip Easer. Rinse Thoroughly. Allow floor to dry.
2. Apply 3 thin coats of Zep Ovation. Allow floor to dry thoroughly between coats; 30 minutes Under normal conditions. If sealer is desired or required because of a porous substrate, use 2 coats of Zeptone or Zeparade Sealer and 2 coats of Zep Ovation.
3. Floor finish is maintained by frequent dust mopping and daily damp mopping with Zep pH Perfect Neutral floor cleaner. Can be spray-buffed using Zep Buff-Up and a red pad with a Zep ZC low speed floor machine.

**WARNING!**

**CAUSES IRRITATION**

Concentrate can cause skin and eye irritation or inflammation. DO NOT swallow this product. Further information on the effects of overexposure is included on the Material Safety Data Sheet, which is available upon request.

Zep advocates limiting exposure to all chemical products. Wearing of tight-fitting safety glasses is recommended, if splashing may occur. If prolonged skin contact is expected, the use of natural rubber, neoprene, nitrile, or other resistant gloves is recommended. Remove contaminated clothing promptly and DO NOT rewear until thoroughly cleaned. After handling, wash hands thoroughly with soap and water.

**FIRST AID:**

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**SKIN:** Flush contaminated skin with plenty of water. Consult a physician if irritation develops.

**INHALATION:** Move exposed person to fresh air. If irritation persists, get medical attention immediately.

**INGESTION:** If this product is swallowed, DO NOT induce vomiting. If vomiting occurs, keep head below hip level to prevent aspiration (breathing) of fluid into the lungs. If affected person is conscious, give plenty of water to drink. Get medical attention at once.

**DISPOSAL AND/OR SPILL INFORMATION:** As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted to a collection vessel, or where permitted, to a sanitary sewer (consult local and state regulations) and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, absorb product on an inert absorbent material, such as Zep-O-Zorb or Zep Super Sorbent, and deposit in a sealable container. Rinse area well with water.

**STORAGE:** Keep this product away from food and food products. Store tightly-closed container in dry area at temperatures between 40° (4°C) and 120°F (49°C).

TOX#035895