



Superior Solutions

PROD. #8042  
708

## PRODUCT SPECIFICATION REPORT

# CAR & TRUCK TOUCH-FREE DETERGENT™

## Touch-Free Detergent for Car and Truck Washing

### DESCRIPTION

An alkaline, medium-foaming, liquid detergent formulated to be used in touch-free car and truck wash facilities.

### FEATURES

- Medium-foaming
- Effective
- Versatile
- Free-rinsing
- Environmentally desirable

### BENEFITS

- Medium foam allows for complete coverage and excellent cling time to vehicle surfaces.
- Penetrates and loosens road film and bug residues without scrubbing.
- Can be used in prep area, presoak shampoo, and wheel and tire wash applications of touch-free and hybrid carwashes.
- Synthetic detergents rinse completely and freely to aid in the elimination of streaking.
- Contains no phosphates, caustics, or acids.

**Note:** When outside temperatures exceed 70°F (41°C), particular attention is needed, to avoid excess contact time and/or drying without proper rinse as paint damage is possible.

### APPLICATIONS

Applied as a prep, pre-soak, shampoo or wheel and tire cleaner in touch-free and hybrid car and truck washing applications. See label for specific use directions and precautionary measures. Use in:

Car Washes  
New & Used Car Dealers

Passenger Car Rental Leasing  
Truck Rental & Leasing

Truck Washes

### COMPANION PRODUCTS

Zep Car Wash shampoos, drying agents, underbody rust inhibitors and clean coat protectants and conditioners, Zep Air Fair fragrances, Zep Spotless, Zep Glass Cleaner, Zep All Around, Zep Enhance-All, Zep Nitrile Gloves, Zep Spectra Clear Glasses

### SPECIFICATIONS

Physical Form .....Liquid  
 Color .....Clear, colorless  
 Odor .....Mild  
 Density/Specific Gravity .....1.05  
 Shelf Life .....1 year minimum

Flash Point (TCC) ..... N/A  
 pH (concentrate) ..... 12.5-13.0  
 D.O.T. Shipping Label ..... None

### PACKAGING

5 Gallon Pail  
20 Gallon Pail  
55 Gallon Pail  
275 Gallon Tote

**Zep Sales & Service, a unit of Zep Inc.**

**1-877-I BUY ZEP**  
**(1-877-428-9937)**



Superior Solutions

# PRODUCT LABEL

PROD. #8042  
708

## CAR & TRUCK TOUCH-FREE DETERGENT™ Touch-Free Detergent for Car and Truck Washing



**BEFORE USING THIS PRODUCT, PLEASE  
READ THIS ENTIRE LABEL.**

**Your One Source for Cleaning &  
Maintenance Products**

**1-877-I-BUY ZEP  
(1-877-428-9937)**

**KEEP OUT OF REACH OF CHILDREN  
FOR INDUSTRIAL AND INSTITUTIONAL  
USE ONLY  
NOT FOR HOUSEHOLD USE OR RESALE**

### PRECAUCION

**AL USUARIO:** Si usted no lee inglés, no use este producto hasta que la etiqueta le haya sido explicada ampliamente.  
**(TO THE USER:** If you cannot read English, do not use this product until the label has been fully explained to you.)

This product is designed exclusively for industrial and institutional use by trained, professional maintenance personnel. Label directions and precautions must be followed exactly. Zep Inc. will not be responsible for any injury, loss or damage if product is used in any manner not in compliance with label directions, or if precautions are not observed.

Zep Inc.  
1310 Seaboard Ind. Blvd.  
ATLANTA, GA 30318  
www.zep.com



### HMS RATINGS

HEALTH	3	4 EXTREME 3 SERIOUS
FLAMMABILITY	0	2 MODERATE 1 SLIGHT
REACTIVITY	0	0 MINIMAL
PERSONAL PROTECTION EQUIPMENT	n,p	Glasses, Gloves

# CAR & TRUCK TOUCH-FREE DETERGENT™

PROD. #8042  
305C

<<<gallons>>>

Zep Car and Truck Touch-Free Detergent is an alkaline, liquid detergent formulated for touch-free and hybrid car and truck wash facilities. Zep Car and Truck Touch-Free Detergent is formulated to have high customer appeal by giving an excellent show on vehicles. Rinses completely and freely, leaving a film-free, shining surface. May also be used as the second step in a two step process. Contains no phosphates, caustics, or acids.

### DIRECTIONS:

When using Zep Car and Truck Touch-Free Detergent, follow directions in accordance with the proper washing season and type of vehicle.

### FOR AUTOMOBILES-PICKUPS:

**WARM WEATHER** (when outside temperatures are 70°F (21°C) or higher) Mix 1 part product with 90-150 parts warm water and apply to vehicle surface under low-pressure spray. Allow a maximum of 1 to 2 minutes contact time before rinsing with high-pressure water. Do not allow to dry on surface.

**COLD WEATHER** (when outside temperatures are less than 70°F (21°C) Mix 1 part product with 70-120 parts warm water and apply to vehicle surface under low-pressure spray. Allow a maximum of 1 to 2 minutes contact time before rinsing with high-pressure water. Do not allow to dry on surface.

**IN A TWO STEP PROCESS** Can be used in a two step process using the above dilutions.

**WHEEL AND TIRE CLEANER** - Mix 1 part product with 5 to 15 parts water and apply to wheels and tires. Allow to soak 15 to 30 seconds and rinse with high-pressure spray. NOTE: Use caution when cleaning polished aluminum or magnesium wheels as streaking may occur.

### FOR TRACTOR / TRAILERS AND OTHER INDUSTRIAL VEHICLES:

Mix 1 part product with 40-90 parts of water, depending on degree and type of soil. Can be applied under high or low pressure. May also be foamed on surfaces. Do not allow to dry on vehicle. Rinse thoroughly. Can be used in two step process using the above dilutions.

**BIODEGRADABLE:** All detergents used in the manufacture of this product are biodegradable.

Dilutions of Zep Car and Truck Touch-Free Detergent should be monitored by using the #9438 Low Alkaline Test Kit.

## DANGER

### CAUSES EYE BURNS

**CAUSES EYE BURNS.** Can cause skin irritation. Harmful if absorbed through skin. DO NOT allow product to contact skin, eyes, or clothing. DO NOT breathe vapors or spray mist. Inhalation of vapors or spray mists can cause respiratory tract irritation. Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and dizziness. DO NOT swallow this product. Repeated exposure can have cumulative effects. Further information on the effects of overexposure is included on the Material Safety Data Sheet, which is available upon request from your employer.

Zep advocates limiting exposure to all chemical products. Wear splash-proof safety goggles during product use and when eye contact is possible. Wear nitrile, neoprene, natural rubber, or other resistant gloves and alkali-resistant footwear; also wear a face shield and rubber apron whenever splashing can occur. For spray applications, use product in well-ventilated areas only; open windows/doors and use exhaust fans. Remove contaminated clothing promptly and DO NOT rewear until thoroughly cleaned. After handling, wash hands thoroughly with soap and water.

### FIRST AID:

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**SKIN:** Immediately flush affected skin with plenty of water for at least 15 minutes. Get medical attention if irritation develops.

**INHALATION:** Move exposed person to fresh air. If irritation persists, get medical attention immediately.

**INGESTION:** If this product is swallowed, DO NOT induce vomiting. If affected person is conscious give plenty of water to drink. Get medical attention at once.

**DISPOSAL AND/OR SPILL INFORMATION:** As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted to a collection vessel, or where permitted, to a sanitary sewer (consult local and state regulations) and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, absorb product on an inert absorbent material, such as Zep Ozorb or Zep Super Sorbent, and deposit in a clean, sealable D.C.T. specification container for disposal as a hazardous waste. Rinse area well with water.

**STORAGE:** Store tightly closed container in dry area at temperatures between 40°F (4°C) and 120°F (49°C).

