



PRODUCT SPECIFICATION REPORT

ZEP X-2400 ASPHALT RELEASE AGENT™

DESCRIPTION

An emulsifying asphalt release agent that has been designed to release polymer modified 'stickier' asphalt.

FEATURES

- Fast Breaking Emulsion
- Economical
- Does not affect asphalt
- Low Temperature Stability
- Excellent Release Properties

BENEFITS

- When applied on the truck bed the release agent quickly separates from the water allowing it to effectively cling to the truck bed for efficient use.
- Concentrated formulation maybe diluted up to 1 to 40 parts water and applied with a low pressure sprayer.
- Product conforms to regulations pertaining to asphalt construction (consult your local ZepRep or DOT regarding specific state approval).
- Product performs well in cold weather conditions.
- No wasted time or product caused by "sticking"

NOTE: This product is not designed to be pre-diluted, it does not have a stable emulsion.

APPLICATIONS

Application Information: Use as a slip coat on beds, walls and tailgates of asphalt trucks and equipment to prevent adhesion of asphalt. Especially used for:

Building Contractors

Equipment Rental & Leasing

Highway Paving Contractors

COMPANION PRODUCTS

Zep Asphalt & Tar Removers, Zep Soy Power, Zep Soy Response, Zep Orange Response, Zep Soy Punch, Zep Cherry Punch, Zep Cherry Bomb, Zep Big Orange, Zep Big Orange-E, Zep E2008 Asphalt Release, Zep Freeze Free Asphalt Release, Zep 70 Lube, Zep Dyna Clean, Zep Dyna 143, Zep Industrial Roll Towels.

SPECIFICATIONS

Physical form	Liquid	Flash point (TCC)	>260°F
Odor	Mild	pH	N/A
Color	Colorless to light amber	Shelf life.....	1 year minimum
Density6.98 lbs/gal		


PACKAGING

- Pail
- Drum



PRODUCT SPECIFICATION REPORT

ZEP X-2400 ASPHALT RELEASE AGENT™



ZEP X-2400™

ASPHALT RELEASE AGENT

PROD.# F126
600B

BEFORE USING THIS PRODUCT, PLEASE READ THIS ENTIRE LABEL.

ZEP MANUFACTURING COMPANY
A division of Acuity Specialty Products Group, Inc.
ATLANTA, GA 30301
*CLEAN ACROSS AMERICA
AND THROUGHOUT THE WORLD™*

AcuityBrands

Your One Source for Cleaning & Maintenance Products

1-877-I BUY ZEP
(1-877-428-9937)

KEEP OUT OF REACH OF CHILDREN FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY
NOT FOR HOUSEHOLD USE OR RESALE

PRECAUCION
AL USUARIO: Si usted no lee inglés, no use este producto hasta que la etiqueta le haya sido explicada ampliamente.
(TO THE USER: If you cannot read English, do not use this product until the label has been fully explained to you.)

This product is designed exclusively for industrial and institutional use by trained, professional maintenance personnel. Label directions and precautions must be followed exactly. Zep Manufacturing Company will not be responsible for any injury, loss, or damage if product is used in any manner not in compliance with label directions, or if precautions are not observed.

HMIS RATINGS		
HEALTH	1	4 EXTREME 3 SERIOUS
FLAMMABILITY	1	2 MODERATE 1 SLIGHT
REACTIVITY	0	0 MINIMAL
PERSONAL PROTECTION EQUIPMENT	B	Glasses, Gloves

DIRECTIONS:

Dilute Zep X-2400 up to 1:30 with water. Some difficult applications may require that the product be used undiluted. Spray onto asphalt contact surfaces to keep asphalt from sticking. Solution can be applied with air and water pressure systems or with hand sprayer. Reapply solution as necessary to prevent asphalt adhesion.

WARNING!
CAUSES IRRITATION

Can cause severe eye irritation or inflammation. Inhalation of spray mists or concentrated vapors may cause respiratory tract irritation and/or mild central nervous system depression characterized by headache, dizziness, nausea, or stupor. DO NOT swallow this product. Avoid breathing vapors or spray mist. Exposure may aggravate existing skin or respiratory disorders. Further information on the effects of overexposure is included on the Material Safety Data Sheet, which is available upon request. Zep advocates limiting exposure to all chemical products. Wearing of tight-fitting safety goggles is strongly recommended, especially for contact lens wearers. Wear natural rubber, nitrile, neoprene, or other resistant gloves. Use product in well-ventilated areas only; open windows/doors and use exhaust fans in enclosed spaces. Remove contaminated clothing promptly and DO NOT rewear until thoroughly cleaned. After handling, wash hands thoroughly with soap and water.

FIRST AID:

EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

SKIN: Wash contaminated skin immediately and thoroughly with soap or mild detergent. Apply a skin cream. Consult a physician if irritation develops.

INHALATION: Move exposed person to fresh air. If irritation persists, get medical attention immediately.

INGESTION: If product is swallowed, DO NOT induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration (breathing) of liquid into the lungs. Get emergency medical attention immediately.

DISPOSAL AND/OR SPILL INFORMATION: As with all cleaning and maintenance procedures, run-off from the cleaning or maintenance process should be diverted to a collection vessel and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contaminated and cannot be used, creating the need for disposal, absorb product on an inert absorbent material, such as Zep-O-Zorb or Zep Super Sorbent, and deposit in a sealable container. Thoroughly clean area with detergent solution and rinse well with water.

STORAGE: Store in a cool area away from direct sunlight. Keep container tightly closed at all times when not in use to decrease evaporation of volatile solvents.