

PRODUCT SPECIFICATION REPORT

SELIG

KWIK-SOLV

Fast Evaporating Industrial Degreaser



DESCRIPTION

Zep Kwik-Solv is a pleasantly scented, solvent degreaser used to remove oils, tars, greases and lubricants from surfaces. This product evaporates quickly and will not leave a residue.

FEATURES

- Effective Degreaser
- · Fast Evaporating
- No Residue / No Rinsing
- · Non-chlorinated

Versatile

- The solvent will quickly penetrate and remove oils, greases and soils from surfaces.
- The solvent will dry rapidly allowing work to continue quicker than water-based solvents or cleaners allow.
- Kwik-Solv does not contain any detergents or builders which can leave a residue on surfaces; the solvent evaporates completely, therefore a water rinse is not required.
- May be used as a degreaser, a contact cleaner, or as an A/C flush. This product may be sprayed on or wiped onto surfaces.
- This product does not contain any chlorinated solvents, such as 1,1,1-trichloroethane, perchloroethylene, or methylene chloride.

NOTE: Precautions must be observed to eliminate sources of ignition for liquid and/or vapors.

APPLICATIONS

Use Zep Kwik Solv to remove oil, grease, dirt, lubricants, and tar from circuit boards, electrical contacts, electric motors, machinery parts and electronic equipment. Recommended to:

Auto Repair Facilities Equipment Rental

Electrical Contractors Metal Working Facilities Air Conditioning Services Industrial Equipment Manuf.

COMPANION PRODUCTS

Zep Model B Sprayer, Zepride, Zep Morado, Zep Big Orange, Zep 45, Zep Carb-X, Zep Recirculating Detergent, Zep Flash, Zep Reach, Zep Cherry Bomb, Zep Ultra Wipes

SPECIFICATIONS

Physical formLiquid Flash point (TCC).....<0°F OdorPleasant Shelf life 1 year minimum

DOT Shipping label Flammable Liquid

PACKAGING

22 oz can Gallon 5 Gallon 20 Gallon 55 Gallon



PRODUCT LABEL

SELIG

KWIK-SOLV

Fast Evaporating Industrial Degreaser



AcuityBrands BEFORE USING THIS PRODUCT, PLEASE READ THIS ENTIRE LABEL

KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY NOT FOR HOUSEHOLD USE OR RESALE

The Solutions People since 1896

800-447-3544 800-HI-SELIG

PRECAUCION

AL USUARIO: Si usted no lee inglés, no use este product
hasta que la etiqueta le haya sido explicada ámpliamant
(TO THE USER! If you cannot read English, do not use thi
product until the label has been fully explained to you.)

This product is designed exclusively for industrial and institutional use by trained, professional maintenance personnet. Label directions and precautions must be followed exactly. Selig Industries will not be responsible for any injury, bss, or damage if product is used in any manner not in compliance with label directions, or if precautions are not observed.

HEALTH	2	4 EXTREME
		3 SERIOUS
FLAMMABILITY	3	2 MODERATE
		1 SLIGHT
REACTIVITY	0	0 MINIMAL
PERSONAL PROTECTION EQUIPMENT	В	goggles, gloves, respirator

(WIK-SOLV

FAST EVAPORATING SOLVENT CLEANER/DEGREASER

I FAVES NO RESIDUE • CONTAINS NO CHLORINATED OR AROMATIC SOLVENTS

DIRECTIONS FOR USE DANGER: Do not use with or near energized electrical equipment, such as floor machines, electric motors, etc., unless

eguipment, such as noor macrinnes, electric motors, etc., unless equipment ris explosion-proof.

As a Contact Cleaner: Disconnect power source prior to application. Apply liberally to surface. Selig's Sure Shot or Little Shot Sprayer is judent for product application. Allow to run off. Surface will be clean, dry and residue-free very quickly. When surface is completely dry, unit may be placed back in service.

When surface is completely dry, unit may be placed back in service. As an Electric Motor and Equipment Degregaes; Disconnect power source prior to application. Brush, spray or immerse parts or equipment. Seligs Surf Shot or Attle Shot Sprayermay be used to provide effective product application. Wipe or allow to air dry. When equipment is completely dry and sevoid of solvent vapors, it may be placed back in kerylce. As an Air Conditioning Flush: Use fur gonjunction with a pressurized air conditioning lishing gun to purge oil and dirty residue from air conditioning lines. Make sure lines completely dry prior to recharging. This can be accomplished, if necessary, by compressed, filtered air or nitrogen.



DANGER!



CONTAINS HEPTANE AND ISOPROPYL ALCOHOL. EXTREMELY FLAMMABLE LIQUID & VAPOR. VAPOR MAY CAUSE FLASH FIRE ELIMINATE ALL IGNITION SOURCES. CAUSES IRRITATION. VAPOR HARMFUL.

HARMFUL OR FATAL IF SWALLOWED.

Can cause skin and eye irritation or inflammation. Inhalation of spray mists or vapors may cause respiratory tract irritation and/or central nervous system depression characterized by headache, dizziness, nausea, or stupor. DO NOT swallow this product. DO NOT breathe vapors or spray mist. Exposure may aggravate existing skin or respiratory disorders. Further information on the effects of overexposure is included on the Material Safety Data Sheet, which is available upon request. Selig advocates limiting exposure to all chemical products. Selig strongly recommends wearing tight-fitting safety glasses, especially when wearing contact lenses. Wear natural rubber, nitrile, neoprene, or other resistant gloves. Use product in well-ventilated areas only; open windows/doors and use exhaust fans in enclosed spaces. Remove contaminated clothing promptly and DO NOT rewear until thoroughly cleaned. After handling, wash nands thoroughly with soap and water.

EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Get medical attention immediately. SKIN: Wash contaminated skin immediately and thoroughly with soap or mild detergent. skin immediately and thoroughly with soap or mild detergent. Apply a skin cream. Consult a physician if irritation develops. INHACATION: Move exposed person to fresh air at once. If breathinghas stopped, perform artificial respiration. Get medical attention immediately. INGESTION: If product is swallowed, DO NOT induce voniting, If vomiting occurs, keep head below hips/tol prevent aspiration (breathing) of liquid into the lungs. Get emergency medical attention/immediately.

JSPOSAL AND/OR SPI/L INFORMATION: As with all capting and waitenames reportures runoff from the cleaning.

DISPOISAIL AND/OR SPIJL INFORMATION: As with all bleaning and praintenance procedures, run-off from the cleaning or maintenance process/should be diverted to a collection vessel, and not allowed to soak into the ground or to enter a storm sewer. If this product is spilled or contanyinated and cannot be used, creating the head for disposal, arborb product, on an inert absorbent material and seposit in a clean, selable D.O.T. specification container for disposal as a hazardous waste. Thoroughly clean area with a detargent solution and riyse area well with water. EXTREMELY FLAMMABLE: Keep a/way from theat, Spark, Open Flame, or any source of lignificor/ STORAGE: Store in a cool area away from direct synlight at temperatures between 40°F(4°C) and 120°F (49°C). Keep container tightly closed at all times when not in use to decrease evaporation of volatile solvents



<<<gallons>>>

